

Supplier	Article description			Art. No. / EAN	Warranty	
T.I.P. Technische Industrie Produkte GmbH Siemensstr. 17 74915 Waibstadt Tel.: 07263-9125-0 Fax: 07263-9125-25 www.tip-pumpen.de	Endurance submersible pump DTX 15000			30257	24 Months	
	Master Box Information					
	Master Box dimensions in cm			weight (kg) gross	pack. Unit (pcs.)	
	Width	Depth	Height			
43,0	38,7	40,5	26,0	4		
Article Information						
Color Box dimensions in cm			weight (kg) net / gross	Qty.		
Width	Depth	Height				
20,7	18,6	38,0	5,8 / 6,5	1		

Endurance submersible pump
DTX 15000

quantity / pallet:

quantity / truck:

Description:

The DTX 15000 is a newly developed submersible pump with special features. Guaranteed capability of continuous duty thanks to the ceramic coated motor shaft, therefore also suitable for the circulation of water e.g. in ponds or for the creation of water course. As well as, for draining of basements in the event of flooding, draining of garden ponds and cisterns.

The pump is equipped with a thermal motor protection and an automatic cut-in/-out switch. The max. grain size is up to 22 mm. The pump also contains a special protection grid which prevents fishes from being sucked in and getting harmed. The DTX 15000 also contains an adjustable float switch for manual and automatic operation.

Technical Data:

Nominal performance:	600 Watt
Delivery height	8 m / 0,8 bar
pressure max.:	0,8 bar
Flow rate max.:	250 l/min / 15.000 l/h
Pump housing:	shockproof
Pressure port:	41,91 mm (1¼" AG)
Max. fluid temp.:	35 °C
Power cord:	10 m / H05RN-F
Grain size max.:	22 mm
Submersion depth max.:	7 m
Suction level min.:	30 mm

Scope of delivery:

hose connector 32 mm - 39,59 mm (1¼"), female, with protective grid for ponds with fishes

Approval marks:

